

TEMPERATURE RISE DOORS

SERIES: TR1800

Approved by UL for up to 3 hours of positive pressure (including negative pressure), steel door, UL10c, ULC CAN4-S104-M80, for single doors up to 4' x 8'. Warnock Hersey has certified the core for up to 1.5 hours of positive and negative pressure for double doors up to 8' x 8'



Standard Features

- Manufactured in 18-gauge sheets - G40 Galvanized or AZ40 galvalume.
- Inverted closing channels, welded at the top and bottom of the door, 16-gauge.
- Both edges beveled to 1/8".
- Core in Pyrophobic tempRCORE*

Main Features

- Door Thickness: 1-3/4".
- Closing seam.
- Primer-Coated Finish.

Fire Resistance

- Fire-rated of up to 180 minutes, UL certified .

Hardware Reinforcements

- Hinges: 10 Gauge.
- Door Closers: 12 Gauge .
- Lock: 16 Gauge.

Optional

- Galvanized Steel G90.
- Power-Coating Finishes.
- Non-standard sizes.

FLEXIBLE CUSTOM SIZES AND FINISHES



Standard Colors:



Embossed Black
Ral 9005



Embossed Brown
Ral 8019



Gray
Ral 7012



Embossed Gray
Ral 7004



Red
Ral 3001



Embossed Beige
Ral 1013



Embossed White
Ral 9003



Matte White
Ral 9003