


STEEL STIFFENED DOORS

REINFORCED DOOR, WITH VERTICAL REINFORCEMENTS




Ruggedly designed to withstand even the most demanding use, this product meets NAAMM specifications. It is manufactured from 22-gauge steel, with reinforcements placed at 6-inch intervals and welded every 5 inches along its length, ensuring optimum structural strength.


Suggested use:

Institutional facilities, Warehouses/factories,
 Transportation terminals, Interior or exterior,
 School/training centers, Public utility stations,
 Government buildings, Manufacturing plants, Vehicle
 service facilities.

DOOR DESIGNS




Flush



Glass Type 1



Glass Type 2




Louver

Steel doors with a thickness of 1-3/4 inches, with a honeycomb core, shall comply with the Steel Door Institute's guide specification, ANSI A250.8.


ANSI A250.8 establishes criteria to ensure that steel doors and frames meet acceptable safety and performance standards in a variety of applications. These standards may include factors such as strength, durability, and the ability to withstand specific environmental conditions. Additionally, these fire-rated doors with a honeycomb core can be manufactured in various gauges to suit specific strength and application requirements.

HARDWARE LOCATIONS




CHANNELS

16 GAGE STEEL
WELDED TO BOTH FACE SHEETS
INVERTED TOP AND BOTTOM




VERTICAL EDGES

VISIBLE SEAM
SPOT WELDS ALONG THE DOOR EDGE
ALLOWS THE INSTALLATION OF ANY TYPE OF
LOCKS




CLOSER REINFORCEMENT

14 GAGE STEEL
CHANNEL 20" LONG




HINGE PREPARATION

4-1/2" HIGH
STANDARD OR HEAVY WEIGHT
FULL MORTISE
HINGE EDGE IS HANDED AND NOT BEVELED




LOCK PREPARATION

GOV. 160/161
CYLINDRICAL TYPE
2-3/4" BACKSET




LOCK PREPARATION

GOV. 86, ANSI/BHMA A115.1
MORTISE TYPE
THE MORTISE REINFORCEMENT FITS ANY
MORTISE LOCK PREPARATION




GLAZING TRIM

FOR ALL FIRE DOORS
3/8" WIDE GLAZING POCKET



FIXED SLAT TYPE LOUVER

FOR 1-3/4" THICK DOOR
12"X24" FIRE RATED
24"X24" FIRE RATED



PRODUCT SPECIFICATIONS:

STANDAR SIZES

WIDTH	HEIGHT
2' - 0"	
2' - 4"	
2' - 6"	
2' - 8"	6' - 8"
2' - 10"	7' - 0"
3' - 0"	7' - 2"
3' - 4"	7' - 10"
3' - 6"	8' - 0"
3' - 8"	
3' - 10"	
4' - 0"	

NOMINAL DOOR OPENING

The 1-3/4-inch thick steel doors, manufactured by FORTIS DOORS, meet the Steel Door Institute's ANSI A250.8 standards.

Doors may have a fire resistance rating of up to three hours, except where glass is installed, which may be subject to limitations based on gauge, size, hardware, construction, etc.

The STEEL STIFFENED DOORS series features visible joints and is constructed with front plates made of cold-rolled commercial-grade steel according to ASTM A1008. Additionally, the option of hot-dip galvanized or galvanized steel according to ASTM A924 and A653 is available.

22-gauge steel vertical bracing (other gauges optional) is placed no more than 6" apart. not more than 6" apart and welded to both front plates not more than 5" apart along their length. along their length. Fiberglass batting insulates the area between the stiffeners. Reinforcements. On occasion, the customer may request internal honeycomb reinforcement, depending on their needs. The top and bottom edges of the door are closed with 16-gauge steel channels welded to both face plates.

FIRE DOORS

UL CERTIFIED UP TO 3 HOURS
OF FIRE RESISTANCE

RATING: 1 HR, 1- 1/2 HR OR 3 HR
MAX. SIZE: 4'0" X 8'0" SINGLE

Regarding hardware, the edges of the hinge boxes are recessed for standard and heavy-duty 4-1/2-inch hinges, with 7-gauge steel reinforcements welded inside the door edge. Various locks can be installed depending on customer needs, with the option of internal plating for security locks, panic locks, fire-rated locks, and customer choice door closers.

For painting, the doors are supplied with a neutral-colored oven-cured primer coat, meeting ANSI A250.10 standards. A custom color option is available but may incur additional costs.

DOOR FACE SHEET	LEVEL	RECOMMENDED DOOR FRAME MATERIAL
20 GAGE STEEL	STANDARD DUTY	16 GAGE STEEL
18 GAGE STEEL	HEAVY DUTY	16 GAGE STEEL
16 GAGE STEEL	EXTRA HEAVY DUTY	16 OR 14 GAGE STEEL
14 GAGE STEEL	MAXIMUM DUTY	16 OR 12 GAGE STEEL